


# SPECIFICATION

ITEM	SP-1500
OUTPUT POWER	CONTINUOUS POWER 1500W      SURGE POWER 3000W
STANDBY CURRENT	DC 12V < 0.5A      DC 24V < 0.4A
INPUT VOLTAGE	DC12V : 10V~16.5V      DC24V : 20V~30V
OUTPUT VOLTAGE	AC 100V, 110V, 120V, 220V, 230V, 240V
OUTPUT WAVEFORM	Modified Sine Wave 
EFFICIENCY	> 85%
※ INITIAL CHECKING	AUTO-DETECTING WRONG BATTERY CONT. ex. 12V / 24V
※ OUTPUT REGULATION	± 5%    INTELLIGENT PWM
※ OUTPUT FREQUENCY	50Hz , 55Hz, 60Hz    CRYSTAL CONTROLLED.
※ COOLING	AUTO-OPERATION FAN
※ OUTPUT SHORT	OUTPUT SHORT CIRCUIT PROTECTION
※ LOW BATTERY	< 10.5V or 21.5V ± 0.5V PRE-ALARM    < 9.5V or 20V ± 0.5V SHUT DOWN & ALARM
※ OVER HEATING	> 60°C PRE-ALARM    > 65°C SHUT DOWN & ALARM
※ OVER LOAD	> 1500W PRE-ALARM    > 1600W SHUT DOWN & ALARM
BATTERY POLARITY REVERSE	BY FUSE
FUSE	DC 12V : 35A * 8PCS      DC 24V : 20A * 8PCS
AC OUTLET	2 AC OUTLETS
DIMENSION (L*W*H)	360*195*80mm
NET WEIGHT	3.5Kg

※ MARK ARE OUR UNIQUE FUNCTIONS