


SPECIFICATION

ITEM	SP-350USB 12/24
OUTPUT POWER	DC12V : CONTINUOUS POWER 300W DC24V : CONTINUOUS POWER 350W
STANDBY CURRENT	DC 12V / 24V < 0.5A
INPUT VOLTAGE OPTIONAL	12/24V AUTO-SWITCH BY MICROCONTROL
INPUT VOLTAGE	DC12V : 10V~15V DC24V : 20V~30V
OUTPUT VOLTAGE	AC 100V, 110V, 120V, 220V, 230V, 240V
USB PORT OUTPUT	5VDC (500mA MAX.)
OUTPUT WAVEFORM	Modified Sine Wave 
EFFICIENCY	> 85%
※ INITIAL CHECKING	AUTO-DETECTING WRONG BATTERY CONT. ex. 12V / 24V
※ OUTPUT REGULATION	+5% / -8% INTELLIGENT AVR
※ OUTPUT FREQUENCY	50Hz , 55Hz , 60Hz CRYSTAL CONTROLLED.
※ COOLING	AUTO-OPERATION FAN
※ OUTPUT SHORT	OUTPUT SHORT CIRCUIT PROTECTION
※ LOW BATTERY PRE-ALARM	< 10.5V ± 0.5V PRE-ALARM < 21V ± 1V PRE-ALARM
※ LOW BATTERY SHUT DOWN	< 9.5V ± 0.5V SHUT DOWN & ALARM < 20V ± 1V SHUT DOWN & ALARM
※ OVER HEATING	> 60°C PRE-ALARM > 65°C SHUT DOWN & ALARM
※ OVER LOAD	> 350W PRE-ALARM > 360W SHUT DOWN & ALARM
BATTERY POLARITY REVERSE	BY FUSE
FUSE	35A *1PC+15A*1PC
AC OUTLET	2 AC OUTLETS EUROPEAN TYPE : 1 AC OUTLET
DIMENSION (L*W*H)	180*73*73mm
NET WEIGHT	1Kg

※ MARK ARE OUR UNIQUE FUNCTIONS

|

|