

Accessory

Description	Features	Photo	Model Name	Dimension (WxHxD)	Length	Application
Remote Control	<ul style="list-style-type: none"> Remote access via user friendly interface ROF (Remote Override Function) / Ignition lockout function 		CR-1	57.0x73.5x26.5 mm 2.24x2.89x1.04 inch	10' / 25'	CX Series
			CR-5	57.0x73.5x26.5 mm 2.24x2.89x1.04 inch	10' / 25'	S1500
			CR-6	130x120x26 mm 5.12x4.72x1.02 inch	10' / 25'	SD Series
			CR-8	57.0x73.5x26.5 mm 2.24x2.89x1.04 inch	10' / 25'	SP Series, SD Series
			CR-10	92.0x92.0x30.5 mm 3.62x3.62x1.20 inch	10' / 25'	SD Series
			CR-16A	98.0x85.0x25.6 mm 3.86x3.35x1.01 inch	10' / 25'	SP Series
			CR-16B	98.0x85.0x25.6 mm 3.86x3.35x1.01 inch	10' / 25'	SL Series, SC Series
			CR-20	149x98x23 mm 5.87x3.86x0.91 inch	10' / 25'	SL Series, SC Series
Rack	<ul style="list-style-type: none"> 19" 2U high rack mount (Max. 4 hot-pluggable modules) Parallel connection up to 8 shelves Easy installation and maintenance 		SR-1600 Rack	446x85x509 mm 17.56x3.35x20.04 inch	—	SR-1600
Temperature Sensor	—		Temperature Sensor	(Temperature Sensor Box) 22.6x12.0x82.2 mm 0.89x0.47x3.24 inch	25'	CX Series